


Part Number: PL-PP24UL



FEATURES:

Planet Patch Panel 24 Port punch down RJ45 Cat6 unshielded in 1U height

Comply with ANSI/TIA-568.2-D, ISO/IEC 11801-1 and

EN 50173-1 Class E specifications..

The clear numbering on both the front and back of each panel gives you a quick and easy way to identify cable runs.

Applications:

- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 100BASE-TX Fast Ethernet
- 10BASE-T Ethernet
- Voice, Video and other applications

Part Number: PL-PP24UL

Technical Specifications:

Panel	1.5mm SPCC with Black color painting
RJ45 Housing	PBT
RJ45 Contact Material & Finished	Phosphor Bronze With 50-60" Nickel plated
	Contact area: Min. 3mm 3" Gold plated
IDC House	PC
IDC Terminal Material & Finished	Phosphor Bronze with 50" Tin-Lead plated. over 50-60" Nickel plated.
	100 & krone tool compatible
	Use for 23-24AWG stranded and solid wire
Jack Bracket Set	ABS Black color
Property	The IDC color combines two wirings of T568A & T568B.
Insertion Force	900 grams for 8 contacts.
Retention Temperature	-30° C to 70° C
Jack Durability	Jack: 750 cycles Plug- Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
IDC Durability	Max, 200 pinching times.
Standards Compliant	The Cat.6 performance is in compliance with the ANSI/ TIA/ EIA 568 B. 2 Standard Jack

