

Planet

Structure Cabling Systems



WELL EXPERIENCED

More than 13 years experience
in networking industry



PROFESSIONAL TEAM

We have professional sales team
to offer fast response and engineers
to support different solutions



ABUNDANT PRODUCTS

Integrated and completed
product lines
for networking and cabling items



STANDARDS COMPLIANCE

ANSI/EIA RS-310-D, IEC2-297,
DIN43494/43491,
GB/T92-3047.2 Metric & ETSI
standard



Part Number: PL-PDU6PUS / PL-PDU8PUS

Planet 19 inch 1U Universal type 6 / 8 way PDU

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 16Ah
- Maximum load capacity 3.5 KW
- Frequency : 50/60 Hz
- Connectors type : Universal Type
- Connectors number : 6/8 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- Lighted master switch



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU6PES / PL-PDU8PES

Planet 19 inch 1U European type 6 / 8 way PDU

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 16Ah
- Maximum load capacity 3.5 KW
- Frequency : 50/60 Hz
- Connectors type : European Type
- Connectors number : 6 /8 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- Lighted master switch



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU6UD / PL-PDU8UD

Planet 19 inch 1U IEC C13 type 6 / 8 way PDU

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 16Ah
- Maximum load capacity 3.5 KW
- Frequency : 50/60 Hz
- Connectors type : IEC C13 Type
- Connectors number : 6/8 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- Lighted master switch



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU6006

Planet 19 inch 1U European type 6 way PDU With Breaker

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 16Ah
- **Maximum load capacity 3.5 KW**
- Frequency : 50/60 Hz
- Connectors type : European Type
- Connectors number : 6 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- 1P Circuit Breaker



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU8008

Planet 19 inch 1U European type 8 way PDU With Surge Protector

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 16Ah
- Maximum load capacity 3.5 KW
- Frequency : 50/60 Hz
- Connectors type : European Type
- Connectors number : 8 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- Lighted master switch
- Surge Protector



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU1607

Planet 19 inch 1U IEC C13 type 16 way PDU With Switch

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 32Ah
- Maximum load capacity 7 KW
- Frequency : 50/60 Hz
- Connectors type : IEC C13 Type
- Connectors number : 18 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- Lighted master switch



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°

Part Number: PL-PDU18VGB

Planet 19 inch 1U European type 18 way PDU With Breaker

Technical Specifications:

- Conforms to DIN49440 and DIN49441
- Length : 19" Inch
- Depth : 1U
- Rated voltage: 110/220V
- Rated current : 32Ah
- Maximum load capacity 7 KW
- Frequency : 50/60 Hz
- Connectors type : European Type
- Connectors number : 18 Way
- Material: Aluminum Alloy
- Power cord length : 1.5/2M
- 2P Circuit Breaker



Certificates:

- RoHS compliant
- CE

Environmental Characteristics:

- Operating temperature: 5 - 45 C°
- Operating relative humidity : 5 - 95 %
- Storage temperature : -25 - 65 C°



 **Planet Structure Cabling Systems Inc.**

 **Montreal, CANADA**

 **info@planet-ca.com**

 **+1 438 990 0820**



www.planet-ca.com