

Part Number PL-FOPWMM24 / PL-FOPWMM48



Product Description:

- Available for small capacity communication system, wall mounting, reasonable and compact structure, harmonized with machine room.
- The cabinet is composed of two parts, one links with optical cables for fusion connection between optical cable and fiber pigtail and another links with patch cord.

Applications:

- Fiber to The Point (FTTX)
- Fiber to The Home (FTTH)
- Passive Optical Networks (PON)
- Local Area Networks (LAN)
- Cable Television (CATV)
- Test Equipment

Features:

- Provide fusion and storage appliance for optical cables.
- Reliable protection appliance of fixing, stripping and earthing for optical cables.
- Whole range protected design for fiber lay to ensure the bending radius $\geq 40\text{mm}$
- Provide various accessories to avoid any unexpected damage to the fiber

Technical Specifications:

Environment temperature	-25°Cæ~+45°Cæ
Relative humidity	≤word 85% (30°Cæ).
Atmosphere pressure	70-106KPa
Insulated Resistance	$\geq 32 \times 10\text{M}\Omega/500\text{V}$ (DC)
Intensity	$\leq 15\text{KV}(\text{DC})/1$ minnow spark-over and no flying arc
Fiber bending radium guaranteed more than 40mm	$\geq 40\text{mm}$.