

Part Number: PL-KE3UJ

FEATURES:

Cat.3 UTP Keystone Jack

- Performance conforms to ANSI/TIA 568.2-D, ISO/IEC 11801-1, EN 50173-1 Class Ea specification
- Enhanced circuit board design and improved RJ45 contacts provide superior performance
- Compact design ideal for high density applications: up to 24 keystone jacks can fit into 1U 24 port unloaded patch panel
- Dual IDC connector can accept 22-26 AWG solid cables
- Terminate with 110 or krone tools
- ETL Verified
- RoHS compliant

DRAWING:



CHARACTERISTICS:

Dielectric Strength	1000V RMS for 1min
Current Rating	1.5Amp Max.
Insulation Resistance	10MΩ Min.
Contact Resistance	2mΩ per contact
Temperature Range	-10° to 60
Humidity	10%~90%; non condensing
Material Flame Rating	PC, UL94 V-0
Admissible Conductor	22AWG ~ 26AWG insulation wire
4pin contact PCB Jack	Phosphor bronze, 50µm thick gold plated over nickel plated in contact area
	Operating life Minimum 750 insertions
IDC Contacts	100µ inch nickel plate over phosphor bronze
	Operating life Minimum 250 Re-terminations

APPLICATIONS:

- 1000BASE-TX
- 1000BASE-T
- 100BASE-TX Fast Ethernet
- 10BASE-T Ethernet
- Voice