

Part Number **PL-CHDMO-FC2**



FEATURES:

- 1/3" CMOS Sensor
- Support Warm white (4000K), Light Distance : up to 25m
- Support OSD Menu
- Support DWDR
- Housing: Metal, IP67

| | |
|--|---|
| <p>7 Ua YfU</p> <p>@ o</p> <p>@ k</p> <p>ut o</p> <p>- o</p> <p>U @</p> <p>o o</p> <p>@bg</p> <p>7 0</p> <p>7 #</p> <p>0 u</p> <p>B][\ hJ]g]cb</p> <p>Q# 7</p> <p>@ Q)</p> <p>Light Distance</p> <p>IR Status</p> | <p>° =) ut@ U</p> <p>U #t@ U</p> <p>U #t" o</p> <p>#U \ o o</p> <p>U U U</p> <p>h* OVuo#</p> <p># 7 0</p> <p>h o</p> <p>' -o</p> <p>V\ , Suport Warm white (4000K)</p> <p>up to 25m</p> <p>AGC Auto Control</p> |
|--|---|

Part Number PL-CHDMO-FC2

| Camera Features | |
|------------------------|-------------------------|
| Starlight | N/A |
| Day/Night | Color |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | DNR |
| Coaxial Audio | YES(only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |
| General | |
| Housing | Metal, IP67 |
| Bracket | NO |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 450mA |
| Dimension | ∅ 96 x 91(H) mm |
| Weight | 600g |