


26AWG Stranded Bare Copper | 600 MHz | 10 Gigabit Ethernet | Shielded 8-Way-8-Way

Product Overview

PLANET Category 7 S/FTP Shielded Patch Cords are engineered for high-performance 10 Gigabit Ethernet structured cabling where superior EMI/RFI protection is required. Each twisted pair is individually wrapped with aluminum/polyester foil, while an overall tinned-copper braid surrounds all four pairs to improve crosstalk control, shield continuity and signal integrity. Designed for Category 7 / Class F applications up to 600 MHz and 10GBASE-T channels up to 100 m. Full Class F performance requires IEC 60603-7-7 compliant mated interfaces; a lower-category interface limits the channel accordingly.



Key Features

- Category 7 S/FTP shielded patch cord
- Performance up to 600 MHz
- Supports 10GBASE-T and legacy Ethernet applications
- 26AWG stranded bare copper conductors – No CCA
- Individual aluminum/polyester foil shield around each pair (PiMF)
- Overall tinned-copper braid shield with ≥60% coverage
- Enhanced EMI/RFI, pair-to-pair and alien-crosstalk control
- IEC 60603-7-7 compatible shielded 8-way modular plugs
- 15 µin gold-plated contacts (standard); 30 µin and 50 µin available as options
- Molded strain-relief boot
- Supports PoE, PoE+, and PoE++ subject to compliant channel design
- 100% continuity, wire-map and shield-continuity tested
- PVC standard / LSZH optional

Standards & Compliance

Reference	Requirement / Application
ANSI/TIA-568.2-D	Category 6A backward compatibility; Category 7 is ISO/IEC-defined
ISO/IEC 11801-1	Category 7 / Class F cabling up to 600 MHz
IEC 61156-6	Category 7 work-area / patch-cord cable
IEC 60603-7-7	Shielded Category 7 connector interface up to 600 MHz
IEEE 802.3an	10GBASE-T 10 Gigabit Ethernet
IEEE 802.3af / 802.3at / 802.3bt	PoE / PoE+ / 4-Pair PoE
RoHS / REACH	Subject to applicable certification/declaration

Cable Construction


Parameter	Specification
Product Type	Category 7 S/FTP Shielded Patch Cord
Cable Construction	S/FTP – individually foil-shielded pairs with an overall braid shield
Number of Pairs	4 Twisted Pairs / 8 Conductors
Conductor	100% Stranded Bare Copper
Nominal Conductor Size	26AWG
Typical Strand Construction	7 × 0.20 mm stranded conductor (typical)
Conductor Insulation	HDPE / High-performance PE
Individual Pair Shield	Aluminum/Polyester foil around each individual pair (PiMF)
Overall Braid Shield	Tinned copper braid, ≥60% coverage, surrounding all four foil-shielded pairs
Outer Jacket	PVC Standard / LSZH Optional
Parameter	Specification
Nominal Cable O.D.	7.2 ± 0.3 mm (typical)
Connector Type	Category 7 shielded 8-way, 8P8C; IEC 60603-7-7 compatible
Contact Material	Phosphor Bronze
Gold Plating Thickness	15 µin standard; 30 µin and 50 µin available as options
Wiring Scheme	T568B Standard / T568A available on request
Strain Relief	Molded Boot
Shield Continuity	360° cable-to-connector shield termination

S/FTP Shielding Construction

PLANET Cat7 S/FTP Patch Cord – Construction

Typical Category 7 S/FTP patch cord construction (3D schematic)

PLANET Cat7 S/FTP patch cord combines individual pair foils with an overall tinned-copper braid for superior EMI/RFI protection and reliable Class F performance up to 600 MHz.



Electrical Characteristics

Parameter	Specification
Characteristic Impedance	100 Ω nominal
Frequency Range	1–600 MHz
DC Resistance	Compliant with applicable Category 7 patch-cord requirements
DC Resistance Unbalance	Compliant with applicable Category 7 requirements
Insulation Resistance	Compliant with applicable Category 7 patch-cord requirements
Shield Continuity	Continuous end-to-end
Propagation Delay	Category 7 / Class F compliant
Delay Skew	≤ 45 ns/100 m

Transmission Performance

Designed to meet applicable Category 7 patch-cord and Class F channel transmission requirements over the frequency range of 1–600 MHz, including alien-crosstalk performance required for 10GBASE-T applications. Full Class F classification requires compliant IEC 60603-7-7 mated interfaces.

Parameter	Specification
Insertion Loss	Category 7 / Class F Compliant
NEXT / PSNEXT	Category 7 / Class F Compliant
ACR-N / PSACR-N	Category 7 / Class F Compliant
ACR-F / PSACR-F	Category 7 / Class F Compliant

Parameter	Specification
Return Loss	Category 7 / Class F Compliant
PSANEXT / PSAACR-F	Category 7 / Class F Compliant

EMI / RFI Shielding Performance

Individual aluminum/polyester foil shielding around every twisted pair, combined with an overall tinned-copper braid, provides superior immunity to external EMI/RFI and improved pair-to-pair and alien-crosstalk control up to 600 MHz. Correct 360° connector termination, bonding and grounding practices are required to achieve optimum Category 7 S/FTP shielding performance.

Network & PoE Application Support

Parameter	Specification
10/100/1000BASE-T	Supported
10GBASE-T (IEEE 802.3an)	Supported in a compliant Category 7 / Class F channel
Maximum Frequency	600 MHz
Standard Channel Length	Up to 100 m in a compliant Category 7 / Class F channel
IEEE 802.3af	PoE
IEEE 802.3at	PoE+
IEEE 802.3bt	4-Pair PoE / PoE++ subject to compliant channel design
Backward Compatibility	Category 6A / 6 / 5e applications with compatible interfaces

Mechanical & Environmental

Parameter	Specification
Connector Mating Durability	≥ 750 mating cycles
Minimum Bend Radius	$\geq 4 \times$ cable O.D. under installed conditions
Operating Temperature	-20°C to +60°C (typical)
Standard Jacket	PVC
Optional Jacket	LSZH

Applications

- Data centers and enterprise networks
- Telecommunications and server rooms
- Patch panel-to-switch connections
- 10 Gigabit Ethernet and high-bandwidth networks
- Wi-Fi 6 / 6E / 7 wireless access points
- IP surveillance and access control
- PoE / PoE+ / PoE++ devices
- Industrial and EMI-sensitive installations

Available Colors & Standard Lengths

Parameter	Specification
Colors	Gray, Red, Yellow, Blue, Green
Standard Lengths	0.25 m, 0.5 m, 1 m, 2 m, 3 m, 5 m, 10 m
Custom Options	Additional colors and lengths available upon request

Ordering Information

Product Family	Color Code	Length	Example Ordering Code
Cat7 S/FTP 24AWG	GY = Gray	0.25 m	PL-PC025S7GY
Cat7 S/FTP 24AWG	RD = Red	0.5 m	PL-PC05S7RD
Cat7 S/FTP 24AWG	YW = Yellow	1 m	PL-PC01S7YW
Cat7 S/FTP 24AWG	BL = Blue	2 m	PL-PC02S7BL
Cat7 S/FTP 24AWG	GR = Green	3 m	PL-PC03S7GR
Cat7 S/FTP 24AWG	BK = Black	5 m	PL-PC55S7BK

Packing 1pc / PE bag

length	0.25M	0.5M	1M	2M	3M	5M	10M
quantity/carton	300	250	200	125	100	75	40

Quality Assurance & Testing

Each PLANET Cat7 S/FTP Patch Cord should undergo 100% wire-map, continuity, open/short, miswire, shield-continuity and visual/mechanical inspection. For consultant and tender projects, transmission performance may be verified using an approved Category 7 / Class F certification analyzer. ETL/UL certification could be provided if needed.