

Part Number **PL-CIPMPO-EC4**



FEATURES:

- High quality imaging with 4MP resolution
- Progressive Scan CMOS Sensor"1/3
- Support H.264/H.265/JPEG/AVI/MJPEG Compression
- Minimun Illumination : 0.04Lux, I nfrared Distance : 25m
- Support DWDR
- Metal+Plastic, IP66

Camera	
Image Sensor	Progressive Scan CMOS Sensor "1/3
Resolution	4MP
Effective Pixels	(H)*1440(V)2560
Compression	H.264/H.265/MJPEG
Audio Compression	G711A/U,AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimun Illumination	Color: 0.01 Lux@(F2.0, AGC ON), B/W: 0 Lux with IR
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focal Length & FOV	2.8mm, horizontal FOV 96°, vertical FOV 51°, diagonal FOV 114° 4 mm, horizontal FOV 74°, vertical FOV 55°, diagonal FOV 98° 6 mm, horizontal FOV 49°, vertical FOV 37°, diagonal FOV 63°
Lens Type	Fixed focal lens, 2.8, 4 and 6mm optional
Focus Control	Fixed
Aperture	F2.0
Pixels	3MP

IP Camera

Part Number PL-CIPMPO-EC4

Night Vision	
Supplement Light	20μ x 2PCS
Supplement Light Distance	30M
Supplement Light Status	Auto Control
Supplement Light Power On	Smart, Manual & Timed mode
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, SMTP, UDP, Qos, 802.1x
ONVIF	Support ONVIF 19.12(Profile S/T)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	25fps@1440*2560
Main Stream 2	25fps@1080*1920
Main Stream 3	25fps@720*1280
Sub Stream 1	25fps@480*720
Sub Stream 2	25fps@360*640
Sub Stream 3	25fps@288*352
Tri Stream	N/A
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, Android

Part Number PL-CIPMPO-EC4

AI Function	
Intelligent Analysis	Intrusion Detetion(based on human detection),motion detection based on human detection
Camera Features	
Day/Night	Color/ B&W (IR-CUT
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, Anti Flicker, HLC, Distortion
Full Color	N/A
Corridor Pattern	N/A
Defog Mode	N/A
ROI	N/A
BLC	Support
WDR	DWDR
Motion Detection	Support(support enable the detection based on human (movement only
Privacy Masking	Rectangular Zone 3
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Korean, Polish, French, Japanese, Spanish, Portuguese, Italian, Hebrew, Ukrainian, Arabic, Vietnamese, Thai, Hungarian
Interface	
Audio	Built-in MIC
Alarm	N/A
SD Card Slot	N/A
RS485	N/A
General	
Housing	Metal+Plastic, IP66
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	RH95% Max °C50+ ~ °C20-
Storage Temperature	RH95% Max °C60+ ~ °C20-
Power Source	DC12V±10%, 700mA
Dimension	φ110x95mm
Weight	305g